

SS110 PAN & TILT

Stainless Steel Pan and Tilt Device

Features

- Corrosion Resistant 316 Stainless Steel
- Dependability and Ease of Maintenance
- 10,000ft Operating Depth
- Precision Ball Bearings



Description

The SS110 underwater pan and tilt assembly is designed in a modular configuration and uses high quality precision ball bearings, low backlash gear drives and motors. The high output brushless, synchronous electric motors can operate reliably even after thousands of cycles. These units can operate at a depth of 10,000 feet and are capable of generating impressive amounts of torque on each axis.

The SS110 can operate in any type of harsh environment due to its corrosion resistant 316 stainless steel design which prevents rusting and water ingestion. Communication is supported through RS232, RS422 and RS485 protocols. Users can choose from a range of input connectors.



Specification – SS110 PAN & TILT

MECHANICAL

Gears:	Precision Strain Wave Gearing
Backlash:	36 arc Minutes (approx. 0.5°)
Dimensions:	8.45 in x 6.64 in x 3.68 in (215mm x 169mm x 94mm)
Weight in Air:	19.3lbs (8.7kg)
Weight in Water:	13.7lbs (6.2kg)
Pressure Compensator:	Internal Diaphragm
Position Limits:	(optional) +/-175° Pan, +/-90° Tilt

ENVIRONMENTAL

Operating Depth:	Up to 10,000ft (3,000m) with Internal Compensation Up to 20,000ft (6,000m) with External Compensation
Temperature Range:	-20°C to 50°C (-4°F to 122°F) Operating -30°C to +60°C (-22°F to +140°F) Storage
Housing Material:	316 Stainless Steel
O-ring Material:	Buna
Fastener Material:	316 Stainless Steel

ELECTRICAL

Input Voltage:	24Vdc, 24Vac or 115Vac
Maximum Drive Current:	100mA to 900mA Per Axis (24Vdc serial, speed dependent) 250mA Per Axis (24Vdc analog) 750mA Per Axis (24Vac) 150mA Per Axis (115Vac)
Maximum Static Current:	100mA – 1.2A Per Axis (24Vdc serial, customer selectable) 650mA Per Axis (24Vdc analog) 350mA Per Axis (24Vac) 100mA Per Axis (115Vac)
Maximum Output Torque:	10 ft-lb (14nm) (24Vdc) 13 ft-lb (18nm) (24Vac & 115Vac)
Maximum Payload:	50lbs (23kg)
Output Speed:	RS485 Version 9 steps 1.5 to 7.5 deg/s
Position Feedback:	12 Bit Resolution (approx 0.1°)
Communication:	Analog, RS485, RS422 or RS232
Connector:	Large Selection of Connectors Available

