

## Technical Specifications

|                             |  |
|-----------------------------|--|
| Communication Channels:     | 4  |
| Channel Select:             | Individual                                 |
| Volume Control:             | Individual for uplink/downlink             |
| Configuration:              | 2 wire (Push To Talk) or 4 wire selectable |
| Dimensions:                 | 360 x 290 x 170mm                          |
| Weight:                     | 3.5Kg                                      |
| Power Supply:               | Rechargeable LiPo battery                  |
| Battery Operating Life:     | 6-7 hours                                  |
| Standby Current:            | 170mA                                      |
| Nominal Frequency Response: | 400Hz to 10KHz                             |
| Audio Power Output:         | 7.8W into 80hm                             |
| Loudspeaker:                | 80hm, splashproof                          |
| Panel Microphone:           | Omnidirectional, splash-proof              |
| Recording Output:           | via RCA socket                             |



**Part No: CP4**

### **Portable 4-channel Round Robin Diver Communications System**

The C-Phone 4 has been designed to provide full round robin communications between the tender, 2 working divers and 1 standby diver, with an additional channel that can be used by other personnel such as deck support crew. The clearly labelled panel facia with heavy duty connectors make it easy to operate while providing longevity in service. The C-Phone 4 is housed in a waterproof, ruggedised Storm case and supplied with a heavy duty C-Tecnic headset and charger.

***Applications: Commercial Diving – Search & Rescue  
– Military***